CHAMPION ROTARY TILLER











CHAMPION ROTARY TILLER

MODEL		SRT - 4	SRT - 5	SRT - 6	SRT - 7	SRT - 8	SRT - 9	SRT - 10	SRT - 11	
Overall Length (mm)		1409	1755	2021	2254	2476	2946	3166	3468	
Overall Width (mm)		1017						1266		
Overall Height (mm)		1179						1196		
Tilling Width	mm inch	1260 49.6	1606 63.2	1872 73.7	2105 82.9	2327 91.6	2797 110	3020 118.9	3322 130.8	
Tractor Power	HP	45-60	50-65	60-75	70-85	80-95	85-100	90-105	105-120	
	Kw	34-45	37-48	45-56	52-63	60-71	64-75	67-78	78-89	
3-Point Hitch Type		Cat - II						CAT-II & III		
Frame Off-set (mm / inch)		29 / 1.1	117 / 4.6	9/0.4	28 / 1.1	21 / 0.8	8 / 0.3	62 / 2.4	0	
Number of Tines (L/C - 90x8)		30	36	42	48	54	60	66	72	
Number of Tines (L/C - 80x7)		30	36	42	48	54	60	66	72	
Standard Tine Construction		Curved / Square								
Transmission Type		Gear / Chain Gear								
Max. Working Depth (mm / inch)		225 / 9								
Rotor Tube Diameter (mm / inch)		89 / 3.5						102 / 4		
Rotor Swing Diameter (mm / inch)		521 / 20.5								
Driveline Safety Device		Slip Clutch / Shear Bolt								
Weight	Kg lbs	475 1047	519 1114	567 1250	613 1351	670 1477	737 1624	1006 2217	1052 2319	

The company reserves absolute rights to modify the specifications of machine and components therein without any prior notice.

Tirth Agro Technology Pvt. Ltd. "SHAKTIMAN". Survey No.-108/1. F

"SHAKTIMAN", Survey No.-108/1, Plot No. B, NH-27, Nr. Bharudi Toll Plaza, Bhunava (Village), Taluka: Gondal, Dist.: Rajkot. State: Gujarat - INDIA, Pin - 360 311. Phone: + 91 (2827) 661637 (30 Lines), + 91 (2827) 270 537, Fax: + 91 (2827) 270 457 Email: info@shaktimanagro.com, Web: www.shaktimanagro.com, CIN: U72900GJ2000PTC 038435

Correspondence: Nr. Hotel Krishna Park, N.H. 27, Vavdi, Rajkot - 360 004, Gujarat, India.

Advantages:

- Suitable for all types of soils
- Suitable for deep tillage especially for sugarcane & banana fields
- Available in 4 ft 11 ft width options

Options:

- Gear Box: Single Speed / Multi speed
- Side transmission: Chain Drive / Gear Drive
- Blades: C type / L type
- Drive Shaft: Shear Bolt / Slip Clutch

Rotor RPM Chart

Series	Input RPM	Gear Box	Spur Gear 1	Spur Gear 2	Rotor Speed
Cha (CD)	540	SS	-	-	210
			16	19	177
		MS	17	18	198
			18	17	222
	1000	MS	13	22	230
Cha (GD)	540	SS		-	226
			16	19	191
		MS	17	18	214
			18	17	240
	1000	MS	13	22	248

Standard Gear Pair 16-19







[&]quot;Weight is including safety guards & excluding PTO"
*Accessories shown are not part of standard equipment.