

ORCHARD 200 (STOS-200)

Suitable for 18 & above HP tractors **Uniform spraying with 100% coverage** Proven chemical and labour & time saving **Uniform and effective fine droplets** Suitable for high density horticulture crops More yield, saving: Higher income



Standard Features & Accessories



DIAPHRAGM PUMP

54 lpm pump for uniform pressure, less maintenance



HDPE material: Durable & Long life



BRASS NOZZLE WITH CERAMIC TIPS

Longer Life, fine spraying



550 MM DIAMETER FAN

High Air output with uniform volume from all nozzels



PRESURE CONTROL VALVE Suitable for various canopy sizes

5 mode pressure control valve for different discharge control

SAFETY DEVICE: Pressure relief valve & rubber coupling to protect pump from high pressure and shock loads.

Technical Specification

Model Name	ORCHARD 200 (STOS-200)
Tractor Power (HP)	18 Hp and above
Tractor PTO speed	540 RPM
Machine Attechment	Fixed type special attechment plate & 3 Point Linkage
Machine Weaight (Kgf/lbs)	208 / 458
Machine Overall Diamension (mm)	1590 X 1470 X 1070
Chemical Tank Capacity	200L HDPE Tank
Spray widht (m)	6 meter(3m each side)
Fan	9 blade 550 mm dia.
Agitator	Powder Mixing
Nozzle Type	Two way type brass nozzle provide for accurate delivery of chemical
Nozzle Disc	Ceramic disc 60°, hollow cone
Disc Required Pressure	Hollow cone : Min. 7 bar , Max 40 bar
No of Nozzle	10 Nozle (1.0 ceramic disc + 1.2 ceramic disc)
Diaphragm Pump	550 RPM
	LPM: 54 L/min
	Max. Pressure: 40 bar
Pressure control valve	5 mode imported Pressure control valve for discharge control
Shut off valve	Size: 1"1/4 BSP & Falling capacity 100 L/min
Suction Filter	Size: 1"1/4 BSP capacity 100 L/min
Gear Ratio	Low - 1 : 4 & High - 1 : 5
Air output m3/hr	Max 12,240 m3/hr
Belt Size	V-Belt B36 x 2 Nos.

The company reserves absolute right to modify the specifications of machine and components their in without any prior notice. Accessories shown are not the part of standard equipment.







