

ROUND BALER (SRB-45)



Compact & Reliable

Wider Pickup for More Coverage

Single Click lubrication system

Suitable for Stalks and Straw

Saves Labour, Time and Money



ROUND BALER

Technical Specifications

Characteristics	SRB 60+	SRB 45
Over all dimension (mm)	1335X(1590-1660)X1230	1245X(1686-1826)X1240
Working Width (mm)	925	1030
Ground Clearance (axle height)mm	180	180
Tractor Power (HP) & PTO Speed (rpm)	30-50 (@540 rpm)	27-50 (@540 rpm)
Hitching System	3 point Linkage Cat II	3 point linkage Cat II
No. of tine Bars	5	5
No. of tines	90	90
No. of Rollers	12	10
Bale Size (mm)	Diameter - 610, Width - 915	Diameter - 460 , Width - 1040
Working Capacity (Bales/hr)	55-60*	60-65*
Bale Weight (kg)	17-35**	14-30**
Baler Weight (kg)	550	553 Approx.
Binding twine	Jute / Polypropylene	Jute / Polypropylene
Binding Activation	Auto Binding system with 8-10 winding	Auto Binding system with 8-10 winding
Track Width (mm)	Adjustable trade (1590-1660)	Adjustable trade (1515-1655)
Tyre Size & Ply	16 x 6.5 – 8PR	16 x 6.5 – 8PR
Drive line Safety device	Slip Clutch and shear bolt	Slip Clutch and Shear bolt
Chamber type	Fixed with Steel rollers	Fixed with Steel Rollers

* The company reserves absolute rights to modify the specifications of machine and components there in without any prior notice.

**Accessories shown are not part of standard equipment.



Tirth Agro Technology Private Limited

"SHAKTIMAN", Survey No.-108/1, Plot No. B, NH-27, Nr. Bharudi Toll Plaza, Bhunava (Village), Taluka: Gondal, Dist.: Rajkot. State: Gujarat- INDIA, Pincode-360311

+91 (02827) 234567, 270537 +91 (02827) 270457

✉ info@shaktimanagro.com, 🌐 www.shaktimanagro.com, CIN: U72900GJ2000PTC 038435



World's Largest Manufacturer of Rotary Tiller